



Better Visual

# Network Digital Signage Commercial Display

- 42", 49", 55", 65", 75" Edge-lit LED, Resolution: 1920\*1080, Brightness: 450 cd/m<sup>2</sup>

## Introduction



Betvis professional large format Full HD LCD displays offer a full set of commercial-grade features with superior visual performance and is well-suited for demanding digital signage and corporate environments.

- Full HD resolution (1920\*1080) provide images with life-like detail and panoramic content view
- 450nit brightness, which is well-suited all indoor and semi-outdoor (without sunlight) environments
- Wide viewing angle (178°)
- Energy-Efficient LED Backlight Technology
- Commercial-Grade Reliability and Performance, 24\*7 operation and comes with durable metal bezel
- Comprehensive set of inputs (HDMI, VGA, USB & CVBS)
- Easy Installation & Maintenance

Model		BV-MOMU4211	BV-MOMU4911	BV-MOMU5511
LCD	LCD Size	42"	49"	55"
	Display Area	930.24*523.26mm	1073.78*604mm	1209.6 *680.4mm
	Display Resolution	1920*1080		
	Aspect Ratio	16:9 (H:V)		
	Brightness	450cd/m <sup>2</sup>	450 cd/m <sup>2</sup>	450 cd/m <sup>2</sup>
	Contrast	1200:1		
	Color	8bit, 1.06B colors		
	Response Time	8ms		
	Backlight Life Cycle	≥50,000 hours		
Viewing Angle	178° / 178° / 178° / 178°			
Power	Consumption	45W	70W	100W
	Input	AC 100-240V, 50-60Hz		
Performance	Working Temperature	0°C ~ 50°C		
	Working Humidity	20% ~ 80%		
	Storage Temperature	-20°C ~ 65°C		
	Storage Humidity	10% ~ 90%		
Dimensions	Net Size	986*577*48mm	1121*654*48mm	1256*728*48mm
	Net Weight	12KG	19.5KG	29KG
Others	Speaker	Optional		
	Housing	Metal		
	Front Panel	Tempered Glass		
	Color	Black(default) back, Golden on front		
	Mounting	VESA Holes Mounting in default. Mounting Bracket (optional)		
	Accessories	Power cord, Remote		
LCD Monitor	I/O Ports	HDMI IN*1, VGA *1, USB*1, CVBS*1		

Model		BV-MOMU6511	BV-MOMU7511	BV-MOMU8611
LCD	LCD Size	65"	75"	86"
	Display Area	1428.48 *803.52mm	1650.24*928.26mm	1872 *1053 mm
	Display Resolution	1920*1080		
	Aspect Ratio	16:9 (H:V)		
	Brightness	450cd/m <sup>2</sup>	450 cd/m <sup>2</sup>	450 cd/m <sup>2</sup>
	Contrast	1200:1		
	Color	8bit, 1.06B colors		
	Response Time	8ms		
	Backlight Life Cycle	≥50,000 hours		
Viewing Angle	178° / 178° / 178° / 178°			
Power	Consumption	45W	70W	100W
	Input	AC 100-240V, 50-60Hz		
Performance	Working Temperature	0°C ~ 50°C		
	Working Humidity	20% ~ 80%		
	Storage Temperature	-20°C ~ 65°C		
	Storage Humidity	10% ~ 90%		
Dimensions	Net Size	1476*856*54mm	1692*1012*54mm	1968*1198*54mm
	Net Weight	\	\	\
Others	Speaker	Optional		
	Housing	Metal		
	Front Panel	Tempered Glass		
	Color	Black(default) back, Golden on front		
	Mounting	VESA Holes Mounting in default. Mounting Bracket (optional)		
	Accessories	Power cord, Remote		
LCD Monitor	I/O Ports	HDMI IN*1, VGA *1, USB*1, CVBS*1		



# Network Digital Signage Commercial Display

Better Visual



**Pizza Hut**  
FEATURING HAND-TOSSED CRUST

**MEDIUM PIZZA**     **\$0** Cheese or 1 Topping     **\$0** more per topping     **\$0** Specialty Pizza

**Specialty Pizzas**  
Pepperoni Lover's® • Meat Lover's® • Veggie Lover's®  
Ultimate Cheese Lover's® • Supreme

**Toppings**  
Pepperoni • Italian Sausage • Beef • Pork Sausage  
Ham • Chicken • Bacon • Anchovies • Mushrooms  
Diced Tomatoes • Black Olives • Green Olives  
Green Peppers • Onions • Pineapple • Jalapeños

**Drinks**  
Regular \$0.00     Large \$0.00

**555.591.2245** 

