

Shelf-level digital media LCD Display provides a significant opportunity for point of purchase conversion by engaging with the consumer via animated content. Betvis has a range of shelf edge screens specifically developed for the retail shelf to help customer to create different brand.



- 27.6" cut Display with 500 nits brightness via an LED backlight.
- Full HD resolution (1920*150) provide images with life-like detail and panoramic content view;
- Elevated brightness (500 nit) provides extraordinary color expression and greater visibility;
- Wide viewing angle (178°);
- Stretched LCD Panels are custom built for 32:9 or >3:1 aspect ratio;
- 24*7 operation and dependability with black mura prevention technology restricting panel blackening even after long periods of use.
- Flexibility for installation and applications
- Also available as a panel and kit (without housing) for being integrated into your own designs.

Features

- Cutting LCD Panel of Full HD LCD Panel 1920*150 Resolution
- High Brightness 500nits
- Vanda-proof with Robust Metal Case
- Anti Glare (AG) Glass Optional
- VESA mounting holes are in default, Wall Mounting / Ceiling Mounting Kit Optional /Others Optional
- LAN Daisy Chain Design Specially Design for Metro Application

Model		BV-UW27511	
LCD	LCD Size	27.6"	
	Display Area	698.4mm x 54.56mm	
	Display Resolution	1920*150	
	Aspect Ratio	>3:1	
	Brightness	500 cd/m ²	
	Contrast	1000:1	
	Color	16.7M	
	Response Time	8ms	
	Backlight Life Cycle	≥50,000 hours	
	Viewing Angle	178° / 178° / 178° / 178°	
Android Solution	Android Hardware	CPU	ARM Cortex-A9, Quad-core 1.6GHz
		Memory	DDR-3, 1G
		Storage	NAND Flash 8GB
		Android Version	Android 4.4
		Network	10/100 Mbps Fast Ethernet
		Wi-Fi	Wi-Fi 802.11b/g
		3G/4G	Built-in 3G/4G module (optional)
	I/O ports	RJ45 x 1, USB x 2, Audio out x 1, Remote x 1, Power x 1	
	Digital Signage Software DSM80	Media Support	Image, Video, Audio, Streaming Video, HTML5, Weather, Logo, Social Media, Date,Time.....
Multiple Zone		Support split-screen display	
LCD Monitor Solution	I/O Ports	I/O Ports	HDMI*1
Power	Power Consumption	20W (Max)	
	Power Input	DC 12V, 1.5A	
Performance	Working Temperature	0℃~50℃	
	Working Humidity	10%~95%	
	Storage Temperature	-20℃~65℃	
	Storage Humidity	5%~95%	
Dimensions	Net Size	723.7*82.5*44mm	
	Net Weight	2.8KG	
Others	Speaker	Optional	
	Housing	Metal	
	Color	Black	
	Mounting	VESA Holes Mounting in default. Mounting Bracket (optional)	
	Accessories	Power cord, Remote	

Solutions



All in one Digital Signage



Quad Core
1GB RAM
8GB Storage



Betvis DSM80 CMS Software



All in one Digital Signage



Intel i3, 4G,
64GB SSD
Windows OS



ANY 3rd Party's CMS Software



LCD Monitor Only



DVI

HDMI

VGA

Application

